



# YANMAR



MINI EXCAVATOR

# SV26

**Discover first-class performance in a surprisingly compact package, perfect for urban work and landscaping, even in the most challenging of environments.** Excellent stability and low ground pressure ensures efficiency on all types of terrain while decreasing soil degradation. The largest cab in its class and clever design delivers real operator comfort, while an advanced hydraulic system offers fast performance with real control. A complete protection system boosts durability, and fuel consumption is remarkably low as well.

- **STABILITY & RELIABILITY**
- **COMFORT**
- **HIGH PERFORMANCE**
- **SMOOTH CONTROL**
- **REDUCED FUEL CONSUMPTION**





# TECHNICAL SPECIFICATIONS

**[ WEIGHT +/-2% (EN STANDARDS) ]**

	Cabin		Canopy	
	Weight	Ground pressure	Weight	Ground pressure
Operating weight (rubber/steel tracks)	2 740/2 824 kg	0.27/0.33 kgf/cm <sup>2</sup>	2 600/2 684 kg	0.26/0.32 kgf/cm <sup>2</sup>
Transport weight (rubber/steel tracks)	2 665/2 749 kg	0.26/0.33 kgf/cm <sup>2</sup>	2 525/2 609 kg	0.25/0.31 kgf/cm <sup>2</sup>
With additional counterweight	+ 100 kg	-	+ 100 kg	-

**[ ENGINE & HYDRAULIC SYSTEM ]**

Type	Yanmar Diesel 3TNV82A-BPBVA
Net Power	17,6 kW at 2400 rpm
Gross Power	18,1 kW at 2400 rpm
Maximum pressure	210 bar
1 double piston pump with variable flow	2 x 32,4 l/min
1 gear pump	21,6 l/min
1 gear pump	10,8 l/min

**[ PERFORMANCE ]**

Travel speed	2,9 / 4,8 km/h
Digging force (short arm/long arm)	14,5 kN / 12,7 kN
Digging force (bucket)	24,5 kN
Noise level	LwA: 94 dBA/LpA: 76 dBA

## DIMENSIONS

Overall length	4250/4295* mm	Max. digging depth – Blade lowered	2690/2950* mm
Overall length with blade at the back	4470/4515* mm	Max. digging reach	4460/4710* mm
Overall height	2400/2440* mm	Max. dumping height	2830/2980* mm
Overall width	1550 mm	Boom swinging (base to left/right)	45°/75°
Length of track on ground	1550 mm	Arm length	1150 / 1400* mm
Blade distance	1380 mm	Rear turning radius	1160 mm
Minimum ground clearance	320 mm	Rear turning radius with add. counterweight	1240 mm

\*With long arm

Yanmar Compact Equipment EMEA

GB\_SPEC\_SV26\_1025

[www.yanmar.com](http://www.yanmar.com)**BUILDING  
WITH YOU**